CedarVent by DCI Installation instructions for cedar ventilation

It is important to follow each step within these instructions for proper installation of the CedarVent product. If you need assistance with this product installation, please call DCI Products Monday through Friday 8am- 5 pm est. Our toll free number is 800-622-4455 or contact us via email info@dciproducts.com





Benefits

- 3/8" (Standard size) thick, strong & cost effective solution
- Easy to cut, easy to install & non-corrosive
- Provides the necessary air for cedar to breathe behind the wall or roof surface
- Convenient 3' foot lengths for easy handling
- Can use power nail guns, will not crush

INSTALLATION:

After the roof/wall is prepared with a vapor barrier over the roof decking or plywood surface, install a strip of CedarVent around the perimeter¹ of the roof/wall surface.

Install CedarVent strips at the lower edge of the roof/wall parallel with the ground or vertical to the ground depending on cedar product.

Continue installing pieces, butting each piece against the other until you reach the end.



Install the next parallel CedarVent up approximately 5" or at the next nailing line for your cedar product that is being installed.(The CedarVent installs at the nail lines for your particular roof cedar product)

FOR WALL:

Cedar clapboards - Nail CedarVent over existing vertical studs when installing.

For Wall shakes - Nail CedarVent horizontal over plywood and house wrap.



CedarVent is available in: 3/8", 9/16", 3/4" and custom thicknesses

1 - Perimeter CedarVent[™] on walls should be 3/8" short of the corner posts and soffits to allow air to escape. For roofs, CedarVent[™] can hang over the 3/8" on the perimeter rake and eave areas. Please refer to diagram ***

Please contact us if you would like more information regarding the various applications, usage, product safety or warranty DCI Products Inc 415 South Penn Street Clifton Heights PA 19018 www.dciproducts.com • 800.622.4455 • info@dciproducts.com





CedarVent by DCI Installation instructions for cedar ventilation

It is important to follow each step within these instructions for proper installation of the CedarVent™ product. If you need assistance with this product installation, please call DC Products Monday through Friday 8am- 5 pm est.

Our toll free number is 800-622-4455 or contact us via email info@dciproducts.com



CedarVent Plus Weather Guard Fabric (Perimeter)



Please contact us if you would like more information regarding the various applications, usage, product safety or warranty DCI Products Inc 415 South Penn Street Clifton Heights PA 19018 www.dciproducts.com • 800.622.4455 • info@dciproducts.com